
VEXXIS™ Antennas GNSS-502



HIGH PERFORMANCE ANTENNA FOR TERRESTRIAL APPLICATIONS



PATENTED TECHNOLOGY

The VEXXIS GNSS-500 series antennas provide outstanding circularly polarized, symmetric radiation patterns with superior multipath rejection performance. This is achieved with a patented, multi-point feeding network which provides uniquely low loss and frequency independent amplitude/phase balance. Strictly balancing signals and sequentially feeding the GNSS antenna at multiple points is the key to achieving remarkable performance.

OPTIMIZED FOR TERRESTRIAL APPLICATIONS

The GNSS-502 antenna is designed with a low profile, aerodynamic enclosure, ideal for ground vehicles in applications such as agriculture, machine control and mobile mapping. Magnetic mounts make the antenna easy to install or move between ground vehicle platforms. The combination of intelligent enclosure design along with multi-constellation and L-Band support makes it ideal for any terrestrial application.

RUGGEDIZED FOR CHALLENGING ENVIRONMENTS

The GNSS-502 has been thoroughly tested to withstand even the most challenging environments. It endured over 1000 hours of intense vibration testing to earn its MIL-STD-810G rating. It is also water resistant under heavy rainfall or high pressure spray, ensuring its long survivability under the toughest operating conditions.

FEATURES

- + Supports dual-frequency GPS, GLONASS, Galileo, BeiDou and SBAS signal reception
 - + L-Band signal reception, supporting correction services such as TerraStar
 - + Multi-point antenna feed provides stable phase center and enhanced multipath rejection
 - + Designed for high quality performance when used with NovAtel's STEADYLINE® technology
 - + Low-profile design ideal for machine control applications
-

GNSS-502



PERFORMANCE

Signal Received

GPS	L1, L2
GLONASS	L1, L2
Galileo	E1, E5b
BeiDou	B1, B2
L-Band	

Pass Band (typical)

Upper passband	1569.0 ± 43.0 MHz
Lower passband	1220.0 ± 31.0 MHz

Out-of-Band Rejection

Band edges ± 50 MHz	15 dB (typical)
Band edges ± 100 MHz	25 dB (typical)

LNA Gain 29 dB (typical)

Gain at Zenith (90°)

L1/B1/E1/G1	+4.0 dBic minimum
L2/B2/E5b/G2	+4.0 dBic minimum
L-Band	+4.0 dBic minimum

Gain Roll-Off (from Zenith to Horizon)

L1/B1/E1/G1	12 dB
L2/B2/E5b/G2	12 dB
L-Band	12 dB

Phase Center Stability <5.0 mm

Noise Figure 2.5 dB (typical)

VSWR ≤2.0 : 1

L1-L2 Differential Propagation Delay
7 ns (maximum)

Group Delay Ripple <15 ns

Nominal Impedance 50 Ω

PHYSICAL AND ELECTRICAL

Dimensions 155 mm D × 45 mm H

Weight 450 g

Connector TNC female

Mounting 2 × magnetic mounts
2 × M4 screw inserts

Power

Input voltage +3.3 to +18.0 VDC
Current 20 mA (typical)

ENVIRONMENTAL

Temperature

Operating -40°C to +85°C
Storage -55°C to +85°C

Humidity 95% non-condensing

Salt Fog MIL-STD-810G (CH1), 509.6

Water/Dust Resistance IP67, IP69K

Vibration (operating)

Random MIL-STD-810G (CH1),
514.7 (15 g) Annex E
Procedure 1, Category 24

Shock MIL-STD-810G (CH1),
516.7 (40 g) Procedure 1

Bump IEC 68-2-27 Ea (25 g)

Regulatory Compliance FCC, CE

RoHS EU Directive 2011/65/EU



Tel. 309.291.0966 | www.AutonomousStuff.com
info@AutonomousStuff.com

Version 3 Specifications subject to change without notice.

©2016 NovAtel Inc. All rights reserved.

NovAtel and STEADYLINE are registered trademarks of NovAtel Inc.

VEXXIS is a trademark of NovAtel Inc.

Printed in Canada.

D20659 September 2016

