



## ARS 408-21 Long Range Radar Sensor 77 GHz

### Safe - reliable - robust - very small design

Continental offers a new type of radar sensor, the **ARS 408-21**, as a possible adaption in different application and as entry version of the series 40X.

### Measuring procedure

The rugged **ARS 408-21** sensor from Continental measures independent the distance and velocity (Doppler's principle) to objects without reflector in one measuring cycle due basis of FMCW (Frequency Modulated Continuous Wave) with very fast ramps, with a real time scanning of 17 / sec.. A special feature of the device is the simultaneously measurement of great distances up to 250 m, relative velocity and the angle relation between 2 objects.

### Typical areas of application

- › Anti-collision protection for vehicles of every description (particul. autonomous)
- › Headway control also for far range (vehicles of every description, particularly autonomous)
- › Area monitoring system for far range, e.g. of hazardous or non-accessible areas
- › Classification of objects
- › Object detection, e.g. in confusing or unclear areas
- › Unremarkable object detection by affix a protection cover before it (radome)

### Advantages

- › **Fast and safe:** The **ARS 408-21** dispels with the apparent contradiction between excellent great measuring performance and a high degree of operational safety. The rugged **ARS 408-21** radar sensor is capable of determining the distance to an object in real time scanning and dependent on the driving speed a possible risk of collision.
- › **Reliable:** The **ARS 408-21** radar sensor is fail-safe and able to recognize troubles of the sensor and sensor environment and display it automatically.
- › **Robust and very small design:** By using a radar technology with less complex measuring principle and the development and mass production in automotive supply industry, the design is kept very robust and very small.

# ARS 408-21 Long Range Radar Sensor 77 GHz - Data Sheet

Measuring performance	Comment	to natural targets (non-reflector targets)
Distance range		0.20 ...250 m far range, 0.20...70m/100m@0...±45° near range and 0.20...20m@±60° near range
Resolution distance measuring	point targets, no tracking	Up to 1.79 m far range, 0.39 m near range
Accuracy distance measuring	point targets, no tracking	±0.40 m far range, ±0.10 m near range
Azimuth angle augmentation	(field of view FoV)	-9.0°...+9.0° far range, -60°...+60° near range
Elevation angle augmentation	(field of view FoV)	14° far range, 20° near range
Azimuth beam width (3 dB)		2.2° far range, 4.4°@0° / 6.2°@±45° / 17°@±60° near range
Resolution azimuth angle	point targets, no tracking	31.6° far range, 3.2°@0° / 4.5°@±45° / 12.3°@±60° near range
Accuracy azimuth angle	point targets, no tracking	±0.1° far range, ±0.3°@0° / ±1°@±45° / ±5°@±60° near range
Velocity range		-400 km/h...+200 km/h (- leaving objects...+approximation)
Velocity resolution	target separation ability	0.37 km/h far field, 0.43 km/h near range
Velocity accuracy	point targets	±0.1 km/h
Cycle time		app. 72 ms near and far measurement
Antenna channels / -principle	microstripe	4TX/2x6RX = 24 channels = 2TX/6RX far - 2TX/6RX near / Digital Beam Forming
Operating conditions	Comment	to natural targets (non-reflector targets)
Radar operating frequency band	acc. ETSI & FCC	76...77 GHz
Mains power supply	at 12 V DC / 24 V DC	+8,0 V...32 V DC
Power consumption	at 12 V DC / 10 A fuse	6.6 W / 550 mA typ. and 12 W / 1.0 A @max. peak power
Load dump protection internal		disconnection >60 V and re-start returning to <60 V
Operating-/ storage temperature		-40°C...+85°C / -40°C...+90°C
Life time	acc. LV124 part 2 - v1.3	10000 h or 10 years (for passenger cars)
Shock	mechanical	500 m/s <sup>2</sup> @6 ms half-sine (10 x shock each in +/-X/Y/Z dir.)
Vibration	mechanical	20 [(m/s <sup>2</sup> )/Hz]@10 Hz / 0,14 [(m/s <sup>2</sup> )/Hz]@1000Hz (peak)
Protection rating	ISO 16750 Classification (Trucks) for vibration	IP 6k 9k (dust, high-pressure cleaning) IP 6k7 (10 cm under water), ice-water shock test, salt fog resistant, mixed gas EN 60068-2-60

# ARS 408-21 Long Range Radar Sensor 77 GHz - Data Sheet

Connections	Comment	to natural targets (non-reflector targets)
Monitoring function		self monitoring (fail-safe designed)
Interface	up to 8 ID	1 x CAN - high-speed 500 kbit/s
Housing	Comment	to natural targets (non-reflector targets)
Dimensions / weight	L * W * H (mm) / (mass)	138 * 91 * 31 / app. 320 g
Material	housing front / backcover	PBT GF 30 black (BASF-Ultradur B4300G6 LS sw 15073) / AC-47100 (AlSi12Cu1(Fe)) die cast aluminium or EN AW 5754 (3.535) AlMg3 pressed-formed aluminium
Miscellaneous		
<p>Measuring principle (Doppler's principle) in one measuring cycle due basis of FMCW with very fast ramps independent measurement of distance and velocity</p> <p>Version <b>ARS 408-21</b>            sensor for the industry            CAN protocol for free communication</p> <p>The version -21 allows to set maximum 8 ID's and maximum 8 collision avoidance regions and to change the sensitivity between low and high sensitivity by the user continuously</p> <p><b>Interfaces:</b> The device is fitted with one CAN bus interface. Further interfaces as converter, software adaption are possible on demand and in case of assumption of costs.</p> <p><b>A special software version supports a measurement range up to 1200m (For objects with high RCS and a free field of view)</b></p>		